


# Setup GeoServer

GeoServer includes several styles designed for IMIS. To set up these styles in IMIS, create a workspace and corresponding datastore connecting to the IMIS Database after installing GeoServer. The corresponding information related to the names and other attribute information related to the workspace, stores, layer and styles information including CSS, SLDs, and SQL queries are included and regularly maintained in the technical document section with the filename `geoserver\_document.md` within the documentation sub-directory in the GitHub repository named web-app source code. To create a new workspace, store, layer, and styles in a geoserver, follow the steps as mentioned in Section Creating New Workspace, Store, Layer & Style in Geoserver. Each workspace, store, layer and style must be created to ensure the proper functioning of the map interface. Currently, there is one workspace, nine stores, thirty layers and one hundred and seventeen styles. Each of these must be created as per the geoserver\_document.md values in the newly set up geoserver. Alternatively, the present workspace is also provided in the GitHub repository under the deployment\_documentation in the sub-directory geoserver\_workspace\_setup, which can also be imported into the geoserver through minor modifications to the XML file that is mentioned below.

To launch GeoServer, start the GeoServer service and navigate to <http://localhost:8080/geoserver> in your web browser. This URL directs you to the GeoServer homepage. Log in using the username and password configured during the installation process.



## 5.1 Add New Workspace

After logging into GeoServer, create a new workspace by navigating to the **Workspace** in the left-side menu and selecting **Add new workspace**.



# GeoServer

### About & Status

- Server Status
- GeoServer Logs
- Contact Information
- About GeoServer

### Data

- Layer Preview
- Workspaces
- Stores
- Layers
- Layer Groups
- Styles

### Services

- WMTS
- WCS
- WFS
- WMS

### Settings

- Global
- Image Processing
- Raster Access

## Workspaces

Manage GeoServer workspaces

 Add new workspace  Remove selected workspace(s)

<< < 1 > >> Results 1 to 8 (out of 8 items)

<input type="checkbox"/> Workspace Name
<input type="checkbox"/> cite
<input type="checkbox"/> imis_base
<input type="checkbox"/> it.geosolutions
<input type="checkbox"/> nurc
<input type="checkbox"/> sde
<input type="checkbox"/> sf
<input type="checkbox"/> tiger
<input type="checkbox"/> topp

<< < 1 > >> Results 1 to 8 (out of 8 items)

Add a new workspace, for the workspace add the name of the current database that we are working on. For NameSpace URI add the URI that we are currently working on. In our local deployment NameSpace URI may be localhost:8000

## About & Status

- Server Status
- GeoServer Logs
- Contact Information
- About GeoServer

## Data

- Layer Preview
- Workspaces
- Stores
- Layers
- Layer Groups
- Styles

## Services

- WMTS
- WCS
- WFS
- WMS

## Settings

## New Workspace

Configure a new workspace

### Basic Info

### Security

Name

Namespace URI

The namespace uri associated with this workspace

☐ Default Workspace

☐ Isolated Workspace

Save

Cancel

## 5.2 Add New Store

To add a new store in GeoServer, follow the steps mentioned below

- On the left sidebar, select Stores.
- This will open the main Stores page where existing stores are listed.
- On the Stores page, look for the Add New Store link or button.
- Click Add New Store to open the form for entering the details of the new store.





## Stores

Manage the stores providing data to GeoServer

[Add new Store](#) [Remove selected Stores](#)

<< < 1 2 3 > >> Results 1 to 25 (out of 58 items)

Search







<input type="checkbox"/>	Data Type	Workspace	Store Name	Type	Enabled?
<input type="checkbox"/>		nurc	arcGridSample	ArcGrid	✓
<input type="checkbox"/>		nurc	img_sample2	WorldImage	✓
<input type="checkbox"/>		imis_africa	imis_africa_building_info	PostGIS	✓
<input type="checkbox"/>		imis_africa	imis_atrica_layer_info	PostGIS	✓

It will take you to new data source page where we are working with POSTGIS so we will select that:






## New data source

Choose the type of data source you wish to configure



### Vector Data Sources

-  Directory of spatial files (shapefiles) - Takes a directory of shapefiles and exposes it as a data store
-  GeoPackage - GeoPackage
-  PostGIS - PostGIS Database
-  PostGIS (JNDI) - PostGIS Database (JNDI)
-  Properties - Allows access to Java Property files containing Feature information
-  Shapefile - ESRI(tm) Shapefiles (\*.shp)
-  Web Feature Server (NG) - Provides access to the Features published a Web Feature Service, and the ability to perform transactions on the server (when supported / allowed).

### Raster Data Sources

-  ArcGrid - ARC/INFO ASCII GRID Coverage Format
-  GeoPackage (mosaic) - GeoPackage mosaic plugin
-  GeoTIFF - Tagged Image File Format with Geographic information
-  ImageMosaic - Image mosaicking plugin
-  WorldImage - A raster file accompanied by a spatial data file

### Other Data Sources

-  WMS - Cascades a remote Web Map Service
-  WMTS - Cascades a remote Web Map Tile Service

After this will direct to the page where we will add details about new vector data source, On this page, you'll first encounter the Basic Store Info section.

## Basic Store Info

---

Workspace \*

iims\_base ▼

Data Source Name \*

Description

☒ Enabled

☐ Auto disable on connection failure

- On the Workspace, dropdown select workspace you have created.
- In Data Source Name you need to give the name as given in the GeoServer Documentation in Git Hub Organization.

[Note: While adding store for “layer\_info” make sure you tick “Expose Primary Key” option.]

After this on the connection parameters section:

## Connection Parameters

host \*  
localhost

port \*  
5432

database  
imis\_base

schema  
public

user \*  
postgres

passwd  
\*\*\*

Namespace \*  
http://192.168.1.79:8000

- On database label, put the database name which you are working on.
- On the schema put the schema name you are working on.
- For the user and password, you will put the credentials used for the pgAdmin.

Once finished, click on the apply and then save.

## 5.3 Add New Layers

To add a new layer in GeoServer, follow the steps below




- On the left sidebar, select Stores.
- This will open the main Layers page where existing Layers are listed.
- On the Layers page, look for the Add New Layer link or button.
- Click Add New Layer to open the form for entering the details of the new Layer.

### Layers

Manage the layers being published by GeoServer

[Add a new layer](#) [Remove selected layers](#)

<< < 1 2 3 4 5 > >> Results 1 to 25 (out of 182 items)

<input type="checkbox"/>	Type	Title	Name	Store	Enabled	Native SRS
<input type="checkbox"/>		buildings	imis_africa:buildings_layer	imis_africa_building_info	✓	EPSG:4326
<input type="checkbox"/>		citypolys	imis_africa:citypolys_layer	imis_atrica_layer_info	✓	EPSG:4326
<input type="checkbox"/>		containments	imis_africa:containments_layer	imis_base_fsm	✓	EPSG:4326

To add the new layer select the table you want to add layer to.

## New Layer

Add a new layer

Add layer from iims\_base:imis\_base\_building\_info

You can create

On databases y

Here is a list of

Choose One

- iims\_base:imis\_base\_building\_info
- iims\_base:imis\_base\_fsm
- iims\_base:imis\_base\_grey\_water
- iims\_base:imis\_base\_layer\_info
- iims\_base:imis\_base\_public\_health
- iims\_base:imis\_base\_swm\_payment\_info
- iims\_base:imis\_base\_taxpayment\_info
- iims\_base:imis\_base\_utility\_info
- iims\_base:imis\_base\_waterpayment\_info
- iims\_base:public
- ne:NaturalEarth
- nurc:arcGridSample
- nurc:img\_sample2
- nurc:mosaic

tribute names and types. [Create new feature type...](#)

ing a native SQL statement. [Configure new SQL view...](#)

g\_info'. Click on the layer you wish to configure

Search

Published	name	Action
	ains	Publish
	surveys	Publish
		Publish
	_uses	Publish
		Publish
	_systems	Publish
	_types	Publish
	_ads	Publish
	use_categories	Publish
	water_sources	Publish
	wms_links	Publish

<< < 1 > >> Results 0 to 0 (out of 0 items)

Figure 6 Adding new layer

Once you have chosen the table you can either publish or Configure new SQL view, which you can see in the figure 5.

### 5.6 Resolving CORS Errors in GeoServer

If you encounter a CORS error in the web interface during deployment, follow these steps to resolve it, Locate the following path

C:\Program Files\GeoServer\webapps\geoserver\WEB-INF\web

Open web.xml as administrator, and uncomment the following section

<!-- Uncomment following filter to enable CORS in Jetty. Do not forget the second config block further down. -->

```
<filter>
  <filter-name>cross-origin</filter-name>
  <filter-class>org.eclipse.jetty.servlets.CrossOriginFilter</filter-class>
  <init-param>
    <param-name>chainPreflight</param-name>
    <param-value>>false</param-value>
  </init-param>
  <init-param>
    <param-name>allowedOrigins</param-name>
    <param-value>*</param-value>
```

```

</init-param>
<init-param>
  <param-name>allowedMethods</param-name>
  <param-value>GET,POST,PUT,DELETE,HEAD,OPTIONS</param-value>
</init-param>
<init-param>
  <param-name>allowedHeaders</param-name>
  <param-value>*</param-value>
</init-param>
</filter>

<!-- Uncomment following filter to enable CORS -->
<filter-mapping>
  <filter-name>cross-origin</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>

```

## 5.7 Importing New Workspace, Store, Layer & Style in Geoserver

To streamline the process of importing manually creating the individual workspaces, stores, layers and styles in geoserver, an alternative approach is to import the entire workspace into geoserver directly. The workspace is provided in the GitHub repository.

Download the zip file and follow the instructions provided below to import the existing workspace into geoserver:

Step 1 : After the geoserver has been installed, create a new workspace named “sample\_workspace” with URL 127.0.0.1.

Step 2 : Create a store named “sample\_datastore” with the following details:

- a. Select the PostGIS (PostGIS Database) option
- b. Set the the Workspace as “sample\_worspace”
- c. Set the Data Source Name as “imis\_base\_building\_info”
- d. Set the Host with the IP of the database that has been setup
- e. Set the port that has been used.
- f. Set the database name (base\_imis)
- g. Set the Schema as building\_info.
- h. Set the database username and password that has been used.
- i. Save the Store

Step 3 : Open to the file:

C:\ProgramData\GeoServer\workspaces\sample\_workspace\datastore.xml

Step 4 : Copy the following lines of code:

```
<entry key="passwd">crypt1:dummyCrypt</entry>
```

Step 5 : Download the provided zip file (Repository: Deployment\_Manual, Sub Directory: Geoserver Workspace Setup) and unzip to your local machine.

Step 6 : Navigate to the datastore.xml of each data store and replace the line of code with the

line of code copied in Step 4.

Step 7 : Ensure the following lines of code match the values as well:

```
<entry key="database">{{DATABASE_NAME}}</entry>
```

```
<entry key="host">localhost</entry>
```

```
<entry key="namespace">">127.0.0.1</entry>
```

Step 8 : Once each datastore's passwd key and other values have been updated, copy the entire workspace folder and paste it into the location: C:\ProgramData\GeoServer\workspaces\

Step 9 : Ensure that the folder name matches the workspace you are importing (base\_imis) and that the sub-folder within the folder contains the data stores.

Step 10 : Restart the tomcat service.

Step 11 : Check if the workspace, store, layer and style is present in the geoserver and remove the dummy workspace that was created.

---

Revision #2

Created 3 March 2025 03:55:31 by Bookstack Editor

Updated 3 March 2025 04:00:12 by Bookstack Editor